# UA3 Thin Client

### Power Meets Versatility











"Experience a leap in performance with UA3—offering 30% more power while remaining budget-friendly. Perfectly tailored for diverse industries like government, finance, healthcare, retail and manufacturing."



#### Unleash 30% More Power for Less

With the AMD Ryzen<sup>™</sup> processor, UA3 delivers 30% greater CPU performance without compromising on value, offering unparalleled efficiency for demanding tasks.



UA3 supports 3 multi-displays, 7 USB ports, and unified communication tools, ensuring your workspace operates at peak efficiency



The UA3, powered by AMD's Hardware Validated Boot (HVB), designed to defend against threats, it's the ultimate security solution for today's flexible work environments



From government to finance and manufacturing, UA3 excels in diverse environments, delivering the power and reliability professionals need to succeed

## UA3 **Thin Client**

#### Power Meets Versatility



	Performance		Expandability
CPU	AMD Ryzen™ Embedded R2312 processor 2.7GHz base clock up to 3.5GHz turbo frequency, Dual Core	WiFi (Optional)	<ul> <li>M.2 for WiFi module (E Key)</li> <li>2 external antenna holes reserved</li> <li>Bluetooth 5.3</li> </ul>
Memory	8GB(4GB x2) DDR4-2400MHz dual channel (up to 32GB optional)	Storage	<ul> <li>Onboard 16GB eMMC as default (up to 64GB optional)</li> <li>mSATA slot for SSD installation</li> </ul>
Multiple Display	3 DP 1.4 and 1 USB-C DP Alt Mode (DP 3 alternative) • Up to 3 x 4K60	LAN	RJ-45 10/100/1000Mbps
		USB	4 USB-A 2.0, 2 USB-A 3.2 Gen2, 1 USB-C 3.2 Gen2 with DP Alt Mode
Display Resolution	4K 60Hz (Max)	Audio & Sound	Combo audio jack for headset & internal speaker
Graphic & Multimedia	<ul> <li>AMD Radeon<sup>™</sup> Graphics with up to 3 compute units, 1.2GHz Max</li> <li>HEVC, VP9 and AVC decode</li> </ul>	Smart Card Reader	Built-in Omnikey 3121 smart card reader (Optional)
	<ul><li>support</li><li>Support AVX2 instruction sets</li></ul>	Power	DC 12V/ 5A 60W power adapter

security / Manageability			
Processor Security	<ul><li>AMD Memory Guard</li><li>AMD HVB</li></ul>		
Security Lock	Security lock 3*7mm		
WoL	RJ45 LAN with standby power design supports Magic Packet wake-up event		
ТРМ	Infineon TPM 2.0		

Environment				
Cooling	Passive cooling (Noise-Free)			
Operating Temperature	0 °C to 35 °C, 32 °F to 95 °F in vertical position			
Operating Humidity	20% - 80% non-condensing			
ECO design	30% Post-consumer recycled plastic (PCR) for plastic chassis			

Physical

Dimension (w x h x d) & Weight

- 68 x 195 x 188mm (with foot stand) / 1.12Kg

Note: UltrArmor may update or modify information, • 45 x 188 x 188mm (without foot stand) / 1.07Kg products, or programs without prior notice.